





NANOLED WALL RECESSED ROUND 45mm



Item no longer in the catalogue.

**S.3254**  
1 module LED 6000K 24Vdc DIMMABLE PWM  
Step light wall recessed



Light Source Technical Data

Light source type:	LED
Colour temperature:	6000K
Rated module luminous flux:	80lm
Rated luminaire luminous flux:	29lm
Rated module power:	1.25W
Rated luminaire power:	1.25W
Luminaire efficacy:	23lm/W
Color Rendering Index:	CRI 75

Power Supply Technical Data


Voltage (DC):	24Vdc
See the SIMES power supply accessories list on the following pages	
PWM Frequency	
NB: Do not use the Remote Power Supply operating at a frequency higher than that indicated	<600Hz
Dimmable:	PWM

Temperature and life time Technical Data

LED Lifetime:	L80 B10 70.000h Ta 25°C L80 B10 50.000h Ta 40°C
Lifespan of the LUMINAIRE:	min. 70.000h Ta 25°C min. 50.000h Ta 40°C
Performance ambient temperature:	Tq 25°C
Operating ambient temperature range:	da -20°C a +50°C
Storage temperature range:	da -20°C a +60°C

Technical Installation Data

Electrical insulation class:	III
Protection class IP:	IP67
Mechanical resistance:	IK09
Weight:	0.3Kg
Power cable:	1m - H05RN-F

**NANOLED WALL RECESSED ROUND 45mm****S.3254****SPECS SHEET****LUMINAIRE TYPE**

Wall mounted luminaire. Recessing depth 85 mm. IP rating IP 67

**MATERIAL CHARACTERISTICS**

Polycarbonate structure and diffuser. 2 mm thick front trim in Stainless Steel - Grade AISI 316L with 2,5 -3% molybdenum content, with high resistance against corrosion. The polycarbonate body is cast together with the stainless steel ring as a single piece. Absence of screws (the luminaire is fixed to the recessing box through clips). Recessing box in polypropylene. Mechanical resistance of diffuser IK 09 Maximum load capacity --

**LIGHTING PERFORMANCE**

Polycarbonate diffuser. Lamp fixed position. LOR --

**LOW SURFACE TEMPERATURE**

Surface temperature of glass -- (Ta 25°C)

**RECESSING BOX**

Polypropylene recessing box with cable entry on all 2 sides also allows: 1) Easy wiring; 2) Cable management for IP67 fast connector; 3) Easy access to the fitting for maintenance purposes.

**WIRING**

Luminaire supplied with fast connector. NANOLED wall recessed versions hard wired with H05RN-F cable 1 meter long. Isolation: CLASS III .

Available colours: Stainless steel (cod.19). Weight: 0.3 Kg Glow Wire test: 750°C

**LED module included****NANOLED PATENTED 2013**

**This luminaire contains built-in LED modules. In case of damage or malfunction please contact the manufacturer to receive additional instructions on how to replace and relative spare parts to order. The LED modules cannot be handled in the luminaire by the end user.**

**LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), where uniformity and quality of the light is 70,000 hours referred to L80 B10 Ta 25 ° C (50,000 hours referable to L80 B10 Ta 40°C). Lifespan of the luminaire min. 70.000 hours Ta 25°C, min. 50,000 hours at 40°C. Performance Ambient temperature Tq 25°C. Operating ambient temperature range is from -20°C to +50°C. Storage temperature range from -20°C to +60°C.**